



40QBS-W Series

Chilled Water Cool-Floor Standing
39,000 - 75,000 BTUH



(Optional)



World's No.1 Air Conditioning Expert

www.carrier.co.th

40QBS-W Series



The latest innovation from the world leader in air conditioning, Carrier, introduces the all-new floor standing split air conditioning system. The 40QD, millennium design, inside and out, will provide you with cool comfort via a variety of control functions.



CARR-INTLCD54 (Option)



CARR-INTDT10 WiFi (Option)

ELECTRONIC THERMOSTAT

Standard supplied with new, user friendly, large LCD display CONTROL PANEL easy to read the temperature from distance or even in the dark.

Special features

- SWING MODE with vertical supply grille ensures coolness throughout the room. Easily to maintenance.
- Adjustable Fan Speed with AUTO FAN cools down the room quickly. MICROPROCESSOR enables precise temperature control up to 1 degree Celsius.
- New slim design and new color make 40QBS blended to your decor of any room. Durable anti-rust casing helps the unit last longer.
- Washable filter enhances Indoor Air Quality.

Specification

| Specification (รายละเอียดของเครื่อง) | | Chilled Water Coil - Floor Standing Type (ตั้งพื้น) | | |
|--|-------------------------|---|-------------|-------------|
| Model Name (ชื่อรุ่น) | Indoor (เครื่องภายใน) | 40QBS | | |
| | | 036W | 048W | 060W |
| Cooling Capacity (ความสามารถในการทำความเย็น) | W | 11,694 | 15,358 | 22,069 |
| | Btu/hr. | 39,900 | 52,400 | 75,300 |
| Power Consumption (กำลังไฟฟ้า) | W | 316 | 370 | 370 |
| Power Supply (ระบบไฟฟ้า) | V/Ph/Hz | 220/1/50 | | |
| Operating Current (กระแสไฟฟ้า) | Amp. | 1.48 | 1.68 | 1.68 |
| Indoor Air Circulation, Max. (ปริมาณลมหมุนเวียน) | m ³ /h | 2,040 | 2,720 | 3,400 |
| | cfm | 1,200 | 1,600 | 2,000 |
| Sound Pressure Level (Turbo/Hi/Med/Low) | dB(A) | 53/47/44/41 | 55/49/45/42 | 56/51/46/43 |
| Dimension - Indoor unit (ขนาดของเครื่อง) | Height | mm. 1,800 | | |
| | Wedth | mm. 690 | 780 | |
| | Depth | mm. 330 | 390 | |
| Net Weight (น้ำหนักเครื่อง) | kg. | 83.0 | 98.5 | 102.0 |
| Connecting Pipe - Indoor (ขนาดท่อที่ไซ) | Water Inlet (FPT) | inch 1/2 | | |
| | Water Outlet (FPT) | inch 1/2 | | |
| | Drain O.D. (ท่อน้ำทิ้ง) | inch 3/4 | | |

Note : Cooling Capacity based on 1. Cooling capacity based on Entering water temp. 44 °F /Leaving water temp. 54 °F 2. Water Temperature Rise : 10°F 3. Entering Air Temperature 80°F.db / 67°F.wb 4. High Speed

Performance Data

| Model | Entering Water Temperature (°F) | Entering Air Temperature (°F db / °F wb) | | | | | | | | | | | | | | | |
|-----------|---------------------------------|--|--------|-------|-------|--------|--------|-------|-------|--------|--------|-------|-------|---------|--------|-------|-------|
| | | 76/63 | | | | 78/65 | | | | 80/67 | | | | 82/69 | | | |
| | | TH | SH | GPM | FT.WG | TH | SH | GPM | FT.WG | TH | SH | GPM | FT.WG | TH | SH | GPM | FT.WG |
| 40QBS036W | 40 | 37,000 | 29,200 | 7.37 | 8.03 | 43,000 | 31,200 | 8.57 | 10.46 | 49,400 | 33,200 | 9.84 | 13.35 | 56,000 | 35,200 | 11.16 | 16.67 |
| | 45 | 27,600 | 24,600 | 5.51 | 4.73 | 32,000 | 26,300 | 6.38 | 6.11 | 37,500 | 28,200 | 7.48 | 8.08 | 44,100 | 30,200 | 8.80 | 10.74 |
| | 50 | 20,100 | 20,100 | 4.01 | 2.66 | 23,000 | 22,000 | 4.60 | 3.38 | 27,200 | 23,700 | 5.43 | 4.52 | 31,900 | 25,400 | 6.37 | 5.97 |
| 40QBS048W | 40 | 48,600 | 38,300 | 9.68 | 14.45 | 56,400 | 40,900 | 11.24 | 18.80 | 64,700 | 43,500 | 12.89 | 23.91 | 73,300 | 46,100 | 14.60 | 29.81 |
| | 45 | 36,300 | 32,400 | 7.25 | 8.52 | 42,100 | 34,600 | 8.39 | 11.01 | 49,300 | 37,100 | 9.83 | 14.55 | 57,800 | 39,700 | 11.54 | 19.29 |
| | 50 | 26,400 | 26,400 | 5.27 | 4.79 | 30,300 | 29,000 | 6.06 | 6.11 | 35,800 | 31,100 | 7.15 | 8.14 | 41,900 | 33,300 | 8.37 | 10.74 |
| 40QBS060W | 40 | 69,900 | 53,200 | 13.92 | 12.04 | 80,600 | 56,800 | 16.06 | 15.48 | 92,000 | 60,400 | 18.33 | 19.55 | 103,900 | 64,000 | 20.69 | 24.22 |
| | 45 | 52,100 | 45,000 | 10.40 | 7.08 | 61,000 | 48,100 | 12.18 | 9.32 | 71,100 | 51,400 | 14.18 | 12.19 | 82,800 | 55,100 | 16.52 | 15.95 |
| | 50 | 37,800 | 37,300 | 7.54 | 3.96 | 43,900 | 40,200 | 8.76 | 5.14 | 51,600 | 43,200 | 10.31 | 6.83 | 61,100 | 46,300 | 12.20 | 9.18 |

Note : Water Temperature Rise 10°F

บริษัท แคนเรียร์ (ประเทศไทย) จำกัด
1858/63-74 ชั้น 14, 15
ถ.เทพรัตน กม. 4.5 แขวงบางนาใต้
เขตบางนา กรุงเทพฯ 10260
โทร. 0-2090-9999 แฟกซ์: 0-2751-4778

Carrier (Thailand) Ltd.
1858/63-74 , 14th, 15th Floor,
Debaratna Road, Km.4.5, Bangna Tai,
Bangna Bangkok 10260 Thailand
Tel. 0-2090-9999 Fax: 0-2751-4778

บริษัทฯ ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า
Carrier reserves the right to make changes in specifications without prior notice.



YOUR CARRIER MAN :